



1. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008
2. THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION WITH A 1.6mm THICK CIRCUIT BOARD.

PT. NO.	PARTS NAME	MATERIAL	Q'TY	NOTE
1	HOUSING	PBT RESIN GLASS REINFORCED (UL94V-0)	1	COLOR : BLACK
2	SLIDER		1	
3	CONTACT	PHOSPHOR BRONZE	n	PLATING : Sn Ni UNDER PLATED (LEAD FREE)

n : NO. OF CONTACTS

mat'l. code				surface 58 / tolerance ISO 1302 / ISO 406 / ISO 1101		projection		product family 58KF		CODE JP	
ltr ecn no dr date				tolerances unless otherwise specified		mm		title			
A	J05-0435	H.T	7/8/'05	angles linear ±0.3		mm		1.25mm SPACING FPC/FFC CONNECTOR			
B	J05-0733	H.T	10/28/'05			scale X		(Cat. No. SLD__S-1LF)			
C	J06-0503	H.T	11/28/'06					dwg no JSA 96550		sheet 1 of 1 size A4	
				dr <i>K. Shouji</i> 11/28/06				type Product Customer Drawing			
				engr <i>K. Shouji</i> 11/28/06							
				chr <i>K. Shouji</i> 11/28/06							
				appd <i>J. Didam</i> 11/28/06							
sheet index		revision C								Rev. C	
		sheet 1								D	



FCIconnect.com

Copyright FCI.