



PART NO.	"L" BODY LENGTH	"A" BODY DIAMETER	"B" STUD LENGTH	"C" NOT THREADED	"D" INSERT DEPTH	THREAD
TNSP4-12-632	3/4 (19.1)	1/4 (6.4)	1/4 (6.4)	1/16 (1.6)	11/64 (4.4)	#6-32
TNSP4-16-632	1 (25.4)					
TNSP4-20-632	1-1/4 (31.8)					
TNSP4-24-632	1-1/2 (38.1)					
TNSP4-28-632	1-3/4 (44.5)					
TNSP4-32-632	2 (50.8)					
TNSP6-16-832	1 (25.4)	3/8 (9.5)	1/4 (6.4)	1/16 (1.6)	3/16 (4.8)	#8-32
TNSP6-20-832	1-1/4 (31.8)					
TNSP6-24-832	1-1/2 (38.1)					
TNSP6-28-832	1-3/4 (44.5)					
TNSP6-32-832	2 (50.8)					
TNSP6-36-832	2-1/4 (57.2)					
TNSP6-40-832	2-1/2 (63.5)					
TNSP8-14-1024	7/8 (22.3)	1/2 (12.7)	9/32 (7.1)	3/32 (2.4)	3/16 (4.8)	#10-24
TNSP8-20-1024	1-1/4 (31.8)					
TNSP8-24-1024	1-1/2 (38.1)					
TNSP8-28-1024	1-3/4 (44.5)					
TNSP8-32-1024	2 (50.8)					
TNSP8-36-1024	2-1/4 (57.2)					
TNSP8-40-1024	2-1/2 (63.5)					
TNSP10-20-1/420	1-1/4 (31.8)	5/8 (15.9)	7/16 (11.1)	1/8 (3.2)	21/64 (8.3)	1/4-20
TNSP10-24-1/420	1-1/2 (38.1)					
TNSP10-28-1/420	1-3/4 (44.5)					
TNSP10-32-1/420	2 (50.8)					
TNSP10-36-1/420	2-1/4 (57.2)					
TNSP10-40-1/420	2-1/2 (63.5)					

NOTES:

- MATERIAL: NYLON 6/6 UL 94 V-2 (RMS-01),
COLOR: WHITE.
THREADED INSERTS/STUDS: BRASS (RMS-231).
- VOLTAGE BREAKDOWN >45,000 VOLTS (>360 VOLTS/MIL)
PER ASTM-D-149-97A

H	SEE CO 200111 FOR CHANGES	SK 01.21.08
-	SEE ENG FOR REV A-G	-----
REV	DESCRIPTION	ENGR DATE

TITLE: THREADED NYLON STURDIPOST				⊕	⊖	DWG IN IN (MM)	QR
TOLERANCES UNLESS NOTED .XX=±.010 .XXX=±.005 FRAC=1/64 ANG=1°	FILE # TNSP	DWN: P.B.	APP:	FINAL			
	MAT'L: SEE NOTES	DT: 08-02-94	DT:	PART #		PRINT TYPE	
	RE: RICHCO, INC.	RICHCO INC. PO BOX 804238, CHICAGO, 60680 (773) 539-4060		SEE TABLE		CA	