

# 1-207369-1 Product Details



1-207369-1



Active

## CPC Connectors



[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

### Product Highlights:

- Connector
- Number of Positions = 28
- Receptacle
- Pin
- Preloaded

[View all Features](#) | [Find Similar Products](#)

**NEW!**

## Documentation & Additional Information

### Product Drawings:

- [RECEPTACLE ASSEMBLY, POSTED, STD SEX, SERIES 2, 17-2...](#) (PDF, English)

### Catalog Pages/Data Sheets:

- [CIRCULAR CONNECTORS FOR COMMERCIAL SIGNAL AND POWER ...](#) (PDF, English)
- [AMP Circular Connectors for Commercial Signal & Powe...](#) (PDF, English)

### Product Specifications:

- None Available

### Application Specifications:

- None Available

### Instruction Sheets:

- None Available

### CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version J)
- [3D Model](#) (IGES, Version J)
- [3D Model](#) (STEP, Version J)

### Additional Information:

- [Product Line Information](#)

### Additional Product Images:

- [Contact Arrangement](#)

### Related Products:

- [Tooling](#)

[List all Documents](#)

**Product Features (Please use the Product Drawing for all design activity)**

**Product Type Features:**

- [Product Type](#) = Connector
- [Number of Positions](#) = 28
- [Gender](#) = Receptacle
- [Pin/Socket](#) = Pin
- Termination Style = Printed Circuit Board
- [Shell Size](#) = 17
- [Shell Type](#) = All Plastic
- [Product Series](#) = Series 2
- [Thread Size](#) = 5/8 - 24 UNEF-2A
- [Sealed](#) = No
- Mounting Hole Diameter (mm [in]) = 3.81 [.150]
- Recommended Hole Size (mm [in]) = 1.19 [0.047]
- Comment = Posts are 0.43 [.017] offset from centerline of contacts.

**Mechanical Attachment:**

- [Preloaded](#) = Yes
- [VDE Tested](#) = No
- Panel Attachment Method = Square Flange

**Termination Related Features:**

- [Solder Tail Contact Plating](#) = Tin over Nickel
- Termination (Solder) Post Length (mm [in]) = 3.18 [0.125]

**Body Related Features:**

- [Mount Style](#) = Panel

**Contact Related Features:**

- [Contact Mating Area Plating](#) = Gold (30)
- [Standard or Reverse Gender](#) = Standard
- Contact Type = Posted

**Housing Related Features:**

- Housing Material = Thermoplastic
- Housing Color = Black
- Housing Flammability Rating = UL 94V-0

**Configuration Related Features:**

- [Reverse Numbering](#) = Without

**Industry Standards:**

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

**Other:**

- Brand = AMP

[Provide Website Feedback](#) | [Contact Customer Support](#)

[Home](#) | [Customer Support](#) | [Suppliers](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)

© 2007 Tyco Electronics Corporation All Rights Reserved

