Web site: www.LairdTech.com

<u>All Categories</u> > <u>Broadband Split / Snap-on Ferrite Cores for Round Cables</u> > <u>Broadband Solid Ferrite Cores for Round Cables and Wiring Harnesses</u> > Item # 28B0562-300


Item # 28B0562-300 Broadband Solid Ferrite Cores for Round Cables and Wiring Harnesses

Broadband Solid Ferrite Cores for Round Cables and Wiring Harnesses

Laird Technologies' Cylindrical EMI suppression ferrites provide a cost effective means of reducing common and differential mode EMI. These cores are most frequently used to suppress common mode EMI on the internal and external cable assemblies of electronic equipment. By decreasing the levels of EMI radiated by internal cables, ferrite cores can reduce the cost and amount of overall shielding required to confine EMI within a product's enclosure. They may also be successfully used on power cables that carry digital or analog signaling. To achieve maximum EMI filtering performance in a given application, select a ferrite with an inner diameter most closely matching the outer diameter of the wire or wire bundle to be filtered. The incircuit impedance may be substantially increased by passing 2 turns of the wire conductor through the ferrite core. A typical common mode application might have two conductors passed through a ferrite core. With equal and opposite currents flowing through the core, zero net bias is established through the component, and maximum impedance is thus realized from the ferrite.



larger image



larger image

Specifications

Figure Number	1
Typical Z Ohms at 25 MHz	150
Nominal Z Ohms at 100 MHz	270
Typical Z Ohms at 300 MHz	420
Dimension A	14.27 mm 0.562 in
Dimension B	6.35 mm 0.250 in
Dimension C	28.32 mm 1.115 in
Material Type	Broad Band Material
Product Type Code	Round Cylindrical Cores
Part Size Code	0562
Additional Description	Standard Part