



used for: D-SUB COMBINATION

**NOTES:**

1. METAL SHELLS: STEEL; min. 320µ" TIN
2. INSULATORS: PBT GF UL 94 V-0, GREEN
3. THREADED INSERT: COPPER ALLOY; min. 200µ" TIN over 80µ" NICKEL
4. COLLAR: COPPER ALLOY; min. 200µ" TIN over 80µ" NICKEL
5. MAXIMUM TORQUE VALUE FOR THREAD: 6" LBS
6.   = CRITICAL DIMENSION; SPC

Directive 2002/95/EC  
RoHS  
Compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GMBH DO NOT ALTER CAD DRAWING BY HAND

tolerance		scale: 2:1 (5:1)	
material:		SEE NOTES	
2001	date	name	title:
drawn	17.05.	Parel	<b>D-SUB COMBINATION FEMALE</b> 8W8S with threaded insert
appd.	17.05.	E. Mickenbecker	
norm			
d-old			
rev. description		dwg no: AutoCAD 2000 DIN-A	
name		13K1A253A 3	
date		sh: 1/1	
part no: 3008W8SXX99A30X		CONEC®	