

[High Voltage Insulators](#)

[Brass Spacers & Standoffs](#)

[Brass Swivel Standoffs](#)

[Brass Chassis Fasteners](#)

[Aluminum Spacers & Standoffs](#)

[PC Board Supports](#)

[Nylon Spacers & Standoffs](#)

[Phenolic Spacers & Standoffs](#)

[Ceramic Standoffs](#)

- [Home](#)
- [About](#)
- [Abbatron](#)
- [Products](#)
- [Locate](#)
- [Distributor](#)
- [or](#)
- [Representative](#)
- [Contact Us](#)
- [Request](#)
- [Information](#)
- [Site Map](#)

Solder Lug Terminal Strips--2 Terminal

Electro-tin plated steel lugs are mounted on .062" thick flame retardant phenolic. Standard size specifics:

- Strip width 3/8"
- lug spacing 3/8"
- Mounting Hole .140" ID
- Mounting Screw #6 Miniature:
- Strip width 5/16"
- lug spacing 1/4"
- Mounting Hole .096" ID
- Mounting Screw #3 or 3/32" rivet



STANDARD PART NO.	MINIATURE PART NO.	FIG.	NO. TERMINALS	
			INSULATED	GROUNDING
830	1055	A	2	1
829	1043	B		-
864	1064	C		-
863	1063	D		1
846	1059	E		-
867	1067	F		-

Inventory Search

Cross Reference

UPS Tracking