

Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: B072-008-1

KVM Switch - 8-Port NetCommander 1U Rackmount Cat5 KVM Switch



Highlights

- 8 RJ45 Ports utilize inexpensive Cat5 patch cables
- Expandable control up to 64 servers from a single station
- 3 ways to switch between servers Push buttons, Hot-Keys, On Screen Display menu
- Supports PS2 and USB CPUs
- 1U Rackmountable includes mounting hardware
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Description

Tripp Lite's 8-Port NetCommander 1U Rackmount Cat5 KVM Switch, is the next generation of our cost-effective, feature rich, KVM switches. It's sleek, 1U design and compact size, features RJ45 connection ports that utilize inexpensive Cat5 patch cables, reducing the amount of cable clutter normally found with traditional KVM cabling. Easily switch between CPU's with Push Buttons, Hot-Key commands, or built-in On Screen Display (OSD) menu function. Cascadability allows connection to up to 256 computers. Compatible with PS/2 and USB computers, VGA, SVGA, or XGA monitors, as well as the following OS platforms: DOS, Windows (all versions), LINUX, UNIX, HP UX, and SUN. One year limited warranty.

For Government Purchasers, B072-008-1 is Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

System Requirements

• Computers: The Tripp Lite B078-101-PS2, or B078-101-USB Server Interface Module must be used to connect a server to the server ports on the KVM switch.

Package Includes

- 8-Port NetCommander 1U Rackmount Cat5 KVM Switch
- 6ft Power Cord
- 6ft Serial Cable
- Rackmount Bracket kit

Features

- Powerful: control 1-64 computers from one KVM console
- Extend distance: between computer and switch up to 30 meters/100 ft.
- Rack mountable: sleek, 1U space saving KVM switches
- Innovative CAT5 technology: eliminate cable clutter at the rack
- Multi-layer security: protects your corporate data
- Easy server management: choice of On Screen Display, Hot-key,or push button control
- Multi-platform: PS/2 and USB support
- Easily add IP functionality with Tripp Lites Model B050-000
- Add Tripp Lite Model B021-000-17 for space saving, in-the-rack, LCD, Keyboard and Mouse
- Compact Size: 17"W x 5"D x 1.75"H

- Video Resolution: 1600x1200@75Hz
- Internal Power Supply
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases
- 1-Year Limited Warranty

Specifications

OVERVIEW				
# Of Users	1			
Console	No			
Port Control	Push Buttons, Hotkeys, OSD			
Max CPU	256			
PC/Server	VGA, USB or PS/2			
Cat5 KVM Switch	Yes			
IP Remote Access	YES WITH B050-000 OR B051-000			
PHYSICAL				
Color	Black			
Style	1U Rackmount			
LCD Monitor (in.)	Not Applicable			
CONNECTIONS				
Connector A	HD15 (FEMALE)			
Connector B	(X2) MINI DIN-6 (FEMALE)			
Ports	8			
FEATURES/SPECIFICATION	NS			
BTUs	27.296			

Related Items

Required Products

Product Type	Related Model	Description	Qty.
KVM Switches & Accessories	B078-101-PS2	KVM Switch Accessories - NetCommander PS2 Server Interface Module	1
KVM Switches & Accessories	B078-101-USB	KVM Switch Accessories - NetCommander USB Server Interface Module	1

Optional Products

Product Type	Related Model	Description	Qty.
KVM Switches & Accessories	B072-016-1	KVM Switch - 16-Port NetCommander 1U Rackmount Cat5 KVM Switch	-
Patch Cables	N105-007-GY	7-ft. Cat5e 350MHz Molded Shielded Patch Cable (RJ45 M/M) - Gray	-

Patch Cables	N105-050-GY	50-ft. Cat5e 350MHz Molded Shielded Patch Cable (RJ45 M/M) - Gray	-	
Patch Cables	N105-010-GY	10-ft. Cat5e 350MHz Molded Shielded Patch Cable (RJ45 M/M) - Gray	-	
Patch Cables	N105-025-GY	25-ft. Cat5e 350MHz Molded Shielded Patch Cable (RJ45 M/M) - Gray	-	

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3270.

Copyright © 2010 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.