




### Glass Passivated Single-Phase Bridge Rectifier



Case Style WOG

#### FEATURES

- Ideal for printed circuit boards
- High case dielectric strength
- High surge current capability
- Typical  $I_R$  less than 0.1  $\mu A$
- Solder dip 260 °C, 40 s
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC



RoHS COMPLIANT

#### TYPICAL APPLICATIONS

General purpose use in ac-to-dc bridge full wave rectification for power supply, adapter, charger, lighting ballaster on consumers and home appliances applications.

| PRIMARY CHARACTERISTICS |               |
|-------------------------|---------------|
| $I_{F(AV)}$             | 1.5 A         |
| $V_{RRM}$               | 65 V to 600 V |
| $I_{FSM}$               | 50 A          |
| $I_R$                   | 10 $\mu A$    |
| $V_F$                   | 1.0 V         |
| $T_J$ max.              | 125 °C        |

#### MECHANICAL DATA

Case: WOG

Epoxy meets UL 94V-0 flammability rating

Terminals: Silver plated leads, solderable per J-STD-002 and JESD22-B102

E4 suffix for consumer grade

Polarity: As marked on body

| MAXIMUM RATINGS ( $T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)   |             |               |            |             |             |             |                  |
|--|-------------|---------------|------------|-------------|-------------|-------------|------------------|
| PARAMETER  | SYMBOL      | B40 C1500G    | B80 C1500G | B125 C1500G | B250 C1500G | B380 C1500G | UNIT             |
| Maximum repetitive peak reverse voltage  | $V_{RRM}$   | 65            | 125        | 200         | 400         | 600         | V                |
| Maximum RMS input voltage R- and C-load  | $V_{RMS}$   | 40            | 80         | 125         | 250         | 380         | V                |
| Maximum DC blocking voltage  | $V_{DC}$    | 65            | 125        | 200         | 400         | 600         | V                |
| Maximum peak working voltage   | $V_{RWM}$   | 90            | 180        | 300         | 600         | 800         | V                |
| Maximum non-repetitive peak voltage  | $V_{RSM}$   | 100           | 200        | 350         | 600         | 1000        | V                |
| Maximum repetitive peak forward surge current  | $I_{FRM}$   | 10            |            |             |             |             | A                |
| Maximum average forward output current for R- and L-load free air operation at $T_A = 45\text{ }^\circ\text{C}$ C-load | $I_{F(AV)}$ | 1.6<br>1.5    |            |             |             |             | A                |
| Peak forward surge current single sine-wave on rated load  | $I_{FSM}$   | 50            |            |             |             |             | A                |
| Rating for fusing at $T_J = 125\text{ }^\circ\text{C}$ ( $t < 100\text{ ms}$ )   | $I^2t$      | 12.5          |            |             |             |             | $A^2s$           |
| Minimum series resistor C-load at $V_{RMS} = \pm 10\%$   | $R_t$       | 1.0           | 2.0        | 4.0         | 8.0         | 12          | $\Omega$         |
| Maximum load capacitance + 50 % - 10 %   | $C_L$       | 5000          | 2500       | 1000        | 500         | 200         | $\mu F$          |
| Operating junction temperature range   | $T_J$       | - 40 to + 125 |            |             |             |             | $^\circ\text{C}$ |
| Storage temperature range  | $T_{STG}$   | - 40 to + 150 |            |             |             |             | $^\circ\text{C}$ |

# B40C1500G thru B380C1500G

Vishay General Semiconductor



| ELECTRICAL CHARACTERISTICS ( $T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted) |                                  |        |            |            |             |             |             |               |
|---|----------------------------------|--------|------------|------------|-------------|-------------|-------------|---------------|
| PARAMETER   | TEST CONDITIONS                  | SYMBOL | B40 C1500G | B80 C1500G | B125 C1500G | B250 C1500G | B380 C1500G | UNIT          |
| Maximum instantaneous forward voltage drop per diode                                  | 1.5 A                            | $V_F$  | 1.0        |            |             |             |             | V             |
| Maximum reverse current at rated repetitive peak voltage per diode                    | $T_A = 25\text{ }^\circ\text{C}$ | $I_R$  | 10         |            |             |             |             | $\mu\text{A}$ |

| THERMAL CHARACTERISTICS ( $T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted) |                                    |            |            |             |             |             |                    |
|--|------------------------------------|------------|------------|-------------|-------------|-------------|--------------------|
| PARAMETER  | SYMBOL                             | B40 C1500G | B80 C1500G | B125 C1500G | B250 C1500G | B380 C1500G | UNIT               |
| Typical thermal resistance <sup>(1)</sup>  | $R_{\theta JA}$<br>$R_{\theta JL}$ | 36<br>11   |            |             |             |             | $^\circ\text{C/W}$ |

**Note:**

(1) Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. at 0.375" (9.5 mm) lead lengths with 0.22 x 0.22" (5.5 x 5.5 mm) copper pads

| ORDERING INFORMATION (Example) |                 |                        |               |               |
|--------------------------------|-----------------|------------------------|---------------|---------------|
| PREFERRED P/N                  | UNIT WEIGHT (g) | PREFERRED PACKAGE CODE | BASE QUANTITY | DELIVERY MODE |
| B380C1500G-E4/51               | 1.12            | 51                     | 100           | Plastic bag   |

## RATINGS AND CHARACTERISTICS CURVES

( $T_A = 25\text{ }^\circ\text{C}$  unless otherwise noted)




Figure 1. Derating Curves Output Rectified Current for B40C1500G...B125C1500G




Figure 2. Derating Curves Output Rectified Current for B250C1500G...B380C1500G




Figure 3. Maximum Non-Repetitive Peak Forward Surge Current Per Diode




Figure 5. Typical Reverse Characteristics Per Diode




Figure 4. Typical Forward Characteristics Per Diode





Figure 6. Typical Junction Capacitance Per Diode

## PACKAGE OUTLINE DIMENSIONS in inches (millimeters)





## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.