


CM1812R600R-10

PHYSICAL DIMENSIONS:

A	4.57	[.180]	± 0.25	[.010]
B	3.05	[.120]	± 0.25	[.010]
C	2.36	[.093]	± 0.25	[.010]
D	1.14	[.045]	± 0.13	[.005]
E	0.58	[.023]	± 0.18	[.007]




COMMON MODE ELECTRICAL CHARACTERISTICS:

COMMON MODE Z @ 100 MHz (Ω)	COMMON MODE Z @ 500 MHz (Ω)	DCR (Ω)	CONTINUOUS Rated Current
Nominal (Ref) 60	Nominal (Ref) 85		
Minimum 45	-		
Maximum 75	-	0.005	5,000 mA


NOTES: UNLESS OTHERWISE SPECIFIED

- TAPED AND REELED per CURRENT EIA SPECIFICATIONS 13" REELS, 2500 PCS/REEL.
- COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.
- U.S. PATENT 6,288,626 SHOULD APPEAR ON THE LABEL OF EACH REEL OF PACKAGED PARTS.
- MINIMUM LINE TO LINE RESISTANCE 1 MΩ
- TERMINATION FINISH IS 100% TIN.


Z vs. FREQUENCY (C,N,O)



Z, R, XL vs. FREQUENCY




OBsolete
LAND PATTERNS FOR REFLOW SOLDERING



DURING AND AFTER SOLDERING OPERATION SOLDER MUST NOT BE ALLOWED TO BRIDGE CONTACTS. CONTACT SEPARATION MUST BE MAINTAINED.

RECOMMENDED SOLDERING CONDITIONS



DIMENSIONS ARE IN mm [INCHES].				THIS DOCUMENT CONTAINS INFORMATION WHICH IS PROPRIETARY AND CONFIDENTIAL TO STEWARD. NO PRODUCTION OR PUBLICATION OF THIS DOCUMENT IN WHOLE OR IN PART SHALL BE MADE WITHOUT WRITTEN AUTHORIZATION FROM STEWARD.			
				Steward			
				PROJECT/PART NUMBER: CM1812R600R-10	REV B	PART TYPE: CO-FIRE	DRAWN BY: JRK
B	CHANGE MIN LINE RESISTANCE	09/28/05	JRK	DATE: 03/02/05	SCALE: NTS	SHEET: 2 of 2	
A	ORIGINAL DRAFT	03/02/05	JRK	CAD #	TOOL # CM1812		
REV	DESCRIPTION	DATE	INT	CM1812R600R-10-B			