

Specification Status: Preliminary

Electrical Rating

Voltage: 15V MAX
Current: 100A MAX

Chip Size: 3.9 X 8.2mm

Leads: Nickel 1/4H
0.125mm nominal thickness

Solder: Lead-free

Tape: None

Marking: None




TABLE I. DIMENSIONS:

	A		B		C		D		E		F		G	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
mm:	19.0	21.0	3.8	4.1	0.5	0.7	5.3	6.5	5.3	6.5	2.9	3.1		
in*:	(0.75)	(0.83)	(0.15)	(0.16)	(0.02)	(0.03)	(0.21)	(0.26)	(0.21)	(0.26)	(0.11)	(0.12)		

*Rounded off approximation

TABLE II. PERFORMANCE RATINGS: As measured in Muller Kelvin Clips Model BU-75K.

I HOLD	CURRENT TRIP LIMITS									TIME TO TRIP	REFERENCE RESISTANCE	ONE-HOUR POST-TRIP RESISTANCE	TRIPPED-STATE POWER DISSIPATION					
	AMPS AT 0°C		AMPS AT 20°C		AMPS AT 60°C		AMPS AT --°C		SECONDS AT 20°C, 8.5A					OHMS AT 20°C		WATTS AT 20°C, 15V		
HOLD	HOLD	TRIP	HOLD	TRIP	HOLD	TRIP	HOLD	TRIP	HOLD	TRIP	TYP	MAX	MIN	MAX	MIN	MAX	TYP	MAX
1.7	2.0	4.0	1.7	3.4	1.2	2.5	--	--	--	5	0.044	0.078	0.044	0.114	--	--	--	2.0

Agency Recognitions:
Reference Documents:
Precedence:
Effectivity:
CAUTION:
Materials Information:

UL, TUV, CSA
PS300
This specification takes precedence over documents referenced herein.
Reference documents shall be the issue in effect on the date of invitation for bid.
Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame.

ROHS Compliant



ELV Compliant



Pb-Free

