

Specification Status: Released

Electrical Rating

Voltage: 15V MAX
Current: 100A MAX

Chip Size: 5 x 7mm

Leads: Nickel 1/4H
0.125mm nominal thickness

Tape: Polyester (White)
8mm nominal Width

Solder: Lead-free

Marking: (Color: Green)

— Manufacturer's Mark

XX 120 — Part Identification

□□□□ — Lot Identification




TABLE I. DIMENSIONS:

	A		B		C		D		E		F		G	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
Mm:	24.9	27.1	4.9	5.2	0.6	1.0	5.5	7.5	10.5	12.5	3.9	4.1		
In*:	(0.98)	(1.06)	(0.19)	(0.20)	(0.02)	(0.03)	(0.21)	(0.29)	(0.41)	(0.49)	(0.15)	(0.16)		

*Rounded off approximation

TABLE II. PERFORMANCE RATINGS: As measured in Mueller Kelvin Clips model BU-75K.

I HOLD	CURRENT TRIP LIMITS									TIME TO TRIP	REFERENCE RESISTANCE	ONE-HOUR POST-TRIP RESISTANCE	TRIPPED-STATE POWER DISSIPATION					
	AMPS 20°C HOLD		AMPS AT 0°C		AMPS AT 20°C		AMPS AT 60°C		AMPS AT --°C					OHMS AT 20°C		OHMS AT 20°C		WATTS AT 20°C, 15V
	HOLD	TRIP	HOLD	TRIP	HOLD	TRIP	HOLD	TRIP	HOLD	TRIP	TYP	MAX	MIN	MAX	MIN	MAX	TYP	MAX
	1.2	1.5	3.1	1.2	2.7	0.8	1.8	--	--	--	5		0.085	0.160	0.085	0.220	--	1.2

Agency Recognitions:
Reference Documents:
Precedence:
Effectivity:
CAUTION:

UL, TUV, CSA
PS300
This specification takes precedence over documents referenced herein.
Reference documents shall be the issue in effect on the date of invitation for bid.
Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame.

Materials Information:

ROHS Compliant

Directive 2002/95/EC
Compliant

ELV Compliant

Directive 2000/53/EC
Compliant

Pb-Free

