

[Home](#) > [Products](#) > [By Type](#) > [PolySwitch Resettable Devices](#) > [Product Feature Selector](#) > Product Details

TRF600-160 Product Details



TRF600-160

TE Part Number: RF0071-000



[Active](#)

PolySwitch Resettable Devices



[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Telecom Application
- Family Name = TRF600
- Through Hole Construction
- IH (Room Temperature) = .16 Amps.
- IT (Room Temperature) = .32 Amps.

[View all Features](#) | [Find Similar Products](#)

Documentation & Additional Information

Product Drawings:

- [TRF600-160](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)**Product Type Features:**

- UL Recognized = File No. E74889
- CSA File No. = 78165C
- Comment = Devices are available with 0.5 ohm resistance matching;
Designed for equipment required to meet Telcordia GR-1089, UL60950 and TIA968; can be used for ITU applications.

Electrical Characteristics:

- [IH \(Room Temperature\) \(Amps.\)](#) = 0.16
- [IT \(Room Temperature\) \(Amps.\)](#) = 0.32
- [Vmax Operating \(V\)](#) = 250
- [Rmin \(•\)](#) = 4.00
- [Rmax \(•\)](#) = 10.000
- [R1 Max \[Post Trip\] \(•\)](#) = 18.00
- [Vmax Interrupt \(V rms\)](#) = 600
- [UL Rated Current \(Amps.\)](#) = 3
- Tripped Power Dissipation (Typical) (W) = 1.00
- R (Typical) (•) = 7.00
- UL Rated Voltage (V) = 250

Termination Related Features:

- Construction = Through Hole

Body Related Features:

- Lead Type = Kinked

Contact Related Features:

- Family Name = TRF600

Configuration Related Features:

- Coating = Coated

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- [Operating Temperature \(Max.\) \(°C\)](#) = 85

Operation/Application:

- Application = Telecom

Packaging Related Features:

- Packaging Method = Bulk, Tape & Reel

Other:

- Brand = Raychem