

0501	8427	1434	9970
<p>0501-0-15-XX-30-XX-04-0 Press-fit in 1,45 mounting hole</p>	<p>8427-0-15-XX-30-XX-04-0 Press-fit in 1,45 mounting hole</p>	<p>1434-0-15-XX-30-XX-10-0 Press-fit in 1,4 mounting hole</p>	<p>9970-0-15-XX-30-XX-04-0 Square press-fit for 0,81 ±0,05 plated thru hole</p>

5970	0477/0478																					
<p>5970-X-15-XX-32-XX-04-0 Square press-fit for 0,81 or 1,0 ±0,05 plated thru hole</p>	<table border="1"> <thead> <tr> <th>Basic Part Number</th> <th>U Square</th> <th>Mounting Hole</th> </tr> </thead> <tbody> <tr> <td>5970-1</td> <td>0,71</td> <td>0,81</td> </tr> <tr> <td>5970-2</td> <td>0,86</td> <td>1,0</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>Basic Part Number</th> <th>Board Thickness</th> <th>Length V</th> <th>Length A</th> </tr> </thead> <tbody> <tr> <td>0477-0</td> <td>1,57</td> <td>1,91</td> <td>4,45</td> </tr> <tr> <td>0478-0</td> <td>3,18</td> <td>3,56</td> <td>6,35</td> </tr> </tbody> </table> <p>047X-0-18-XX-30-XX-04-0 Solderless press-fit in 0,97 +0,08 / -0,05 plated thru hole (use 1.1mm drill prior to plating)</p>	Basic Part Number	U Square	Mounting Hole	5970-1	0,71	0,81	5970-2	0,86	1,0	Basic Part Number	Board Thickness	Length V	Length A	0477-0	1,57	1,91	4,45	0478-0	3,18	3,56	6,35
Basic Part Number	U Square	Mounting Hole																				
5970-1	0,71	0,81																				
5970-2	0,86	1,0																				
Basic Part Number	Board Thickness	Length V	Length A																			
0477-0	1,57	1,91	4,45																			
0478-0	3,18	3,56	6,35																			

4612	4613	0680	0149
<p>4612-0-31-XX-30-XX-04-0 Compliant press-fit in 1,02 ±0,08 plated hole. For 1,52 → 2,54 thick board</p>	<p>4613-0-31-XX-30-XX-04-0 Compliant press-fit in 1,02 ±0,08 plated hole. For 2,29 → 3,30 thick board</p>	<p>0680-0-15-XX-32-XX-10-0 Solder mount in 1,3 min. mounting hole</p>	<p>0149-0-15-XX-30-XX-04-0 Press-fit in 1,5 mounting hole</p>

<p>SPECIFICATIONS</p> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>DIMENSION IN INCHES TOLERANCES ON: LENGTHS: ±0,13 DIAMETERS: ±0,05 ANGLES: ± 2°</p>	<p>ORDER CODE: XXXX - X - XX - XX - XX - XX - 0</p> <p>BASIC PART # →</p> <p>SPECIFY SHELL FINISH:</p> <ul style="list-style-type: none"> 01 5,08µm TIN/LEAD OVER NICKEL ◇ 80 5,08µm TIN OVER NICKEL (RoHS) ◇ 15 0,25µm GOLD OVER NICKEL (RoHS) <p>SPECIFY CONTACT FINISH:</p> <ul style="list-style-type: none"> 02 2,54µm TIN/LEAD OVER NICKEL ◇ 84 2,54µm TIN OVER NICKEL (RoHS) ◇ 27 0,76µm GOLD OVER NICKEL (RoHS) <p>SELECT CONTACT</p> <p>#30 or #32 CONTACT (DATA ON PAGES 218 & 219)</p>
---	---