

- Our lowest profile DIP socket with an above PCB height of only .095".
- Special short Hi-Rel, 4-finger BeCu #12 contact is rated at 3 amps. See page 207 for details.
- Series 115 use MM #1534 pins. See page 130 for details.
- Insulators are high temperature thermoplastic.

Total number of pins				Quantity per tube	Ordering Information
	A	B	C		
	.100 (TYP)				

6	0.3	0.3	0.4	68	115-XX-306-41-003000	
8	0.4	0.3	0.4	50	115-XX-308-41-003000	
14	0.7	0.3	0.4	28	115-XX-314-41-003000	
16	0.8	0.3	0.4	25	115-XX-316-41-003000	
18	0.9	0.3	0.4	22	115-XX-318-41-003000	
20	1.0	0.3	0.4	20	115-XX-320-41-003000	
22	1.1	0.3	0.4	18	115-XX-322-41-003000	
24	1.2	0.3	0.4	16	115-XX-324-41-003000	
28	1.4	0.3	0.4	14	115-XX-328-41-003000	
20	1.0	0.4	0.5	20	115-XX-420-41-003000	
22	1.1	0.4	0.5	18	115-XX-422-41-003000	
24	1.2	0.4	0.5	16	115-XX-424-41-003000	
28	1.4	0.4	0.5	14	115-XX-428-41-003000	
24	1.2	0.6	0.7	16	115-XX-624-41-003000	
28	1.4	0.6	0.7	14	115-XX-628-41-003000	
32	1.6	0.6	0.7	12	115-XX-632-41-003000	
36	1.8	0.6	0.7	11	115-XX-636-41-003000	
40	2.0	0.6	0.7	10	115-XX-640-41-003000	
48	2.4	0.6	0.7	8	115-XX-648-41-003000	
50	2.5	0.6	0.7	8	115-XX-650-41-003000	

XX= Plating Code
See Below

For RoHS compliance
select ◇ plating code.

SPECIFY PLATING CODE XX=	13◇	93	99	43◇	44◇
Sleeve (Pin)	10μ" Au	200μ" Sn/Pb	200μ" Sn/Pb	200μ" Sn	200μ" Sn
Contact (Clip)	30μ" Au	30μ" Au	200μ" Sn/Pb	30μ" Au	200μ" Sn