



**Notes:**

1. Electrical Specifications:
  - Meets USB 2.0 Specification
  - Contact Resistance: 30 mOhm max.
  - Insulation Resistance: 1000 MOhm min. @ 100 VDC
  - Current Rating: 1.5 A max. at 25° C
  - Working Voltage: 30 V (RMS) max.
  - DWV: 500 VAC/60s at sea Level
  - Operating Temperature: -40° C to +85° C
2. Material and Finish:
  - Coupling Ring: Zinc Die-Cast, Nickel Plated
  - USB Plug Housing: ABS, UL94 V-0, Nickel Plated
  - Interfacial Seal: Silicone, Color: White
  - Cable Fitting: Brass, Nickel Plated
  - Cable Fitting Rubber Ring: NBR, Color: Black
  - USB Metal Shell: SPCC, Nickel Plated
  - USB Insulator: PBT, UL94 V-0, White
  - USB Contacts: Copper Alloy,
  - USB Contact Finish: 30 u" Gold min. over Nickel for mating area, Tin over Nickel for solder cup
3. USB Type A Plug accepts AWG28 to AWG24 wires, Cable with outer Diameter of 4.06 mm to 5.21 mm
4. Cable Fitting accepts Cable Outer Diameter Range of 4 mm to 8 mm
5. RoHS compliant
6. IP67 rated when fully mated with appropriate mating connector

Directive 2002/95/EC  
"RoHS"  
Compliant

THIS DRAWING MAY NOT BE COPIED, OR REPRODUCED IN ANY WAY AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION. <b>DO NOT ALTER CAD DRAWING BY HAND</b>	Customer:			Tolerance Unless otherwise specified 0 PLC ±0.50 1 PLC ±0.38 2 PLC ±0.25 3 PLC ±0.10 ANGLES ±3°	 Autodesk Inventor	Scale: 1.5:1	Dim. in mm
	Name	Title	Approval Date			Material: See Notes	
						Title: Die-Cast IP67 USB Plug Kit with USB 2.0 Type A Plug Solder Cup Version	
						Drawing No.: 17K1A154	
						Part No.: 17-200591	
	Rev.	Changes	Date	Name			DIN A3 Sheet 1/1