

PART	CONFIGURATION	PART	CONFIGURATION	PART CONFIGURATION	
NUMBER	POS 6 5 4 3 2 1	NUMBER	POS 6 5 4 3 2 1	NUMBER POS 6 5 4 3 2 1	
85761-XY01LF	C	85761-XY11LF	E	85761-XY21LF	
85761-XY02LF	E X - X X - X  D X X X  C X X X X X X X  B X X  A X - X X - X	85761-XY12LF	E X X X X X C C X X X X X X C A X X X X X	85761-XY22LF	
85761-XY03LF	E X X X X X X X X X C X X X X X X X X X	85761-XY13LF	E X X X X X X X X X X X X X X X X X X X	85761-XY23LF	
85761-XY04LF	E	85761-XY14LF	E	85761-XY24LF	
85761-XY05LF	E X SEE C X NOTE 2 B X A X	85761-XY15LF	E X X X X C X X A X X A X X	85761-X025LF	
85761-XY06LF	E X SEE C X NOTE 2 B X A X	85761-XY16LF	E	85761-XY26LF  85761-XY26LF  C	
85761-XY07LF	E	85761-XY17LF	E	E D C B A	
85761-XY08LF	E	85761-XY18LF	E	E D C B A	
85761-XY09LF	E X X X X X C X X X A X X A X X X	85761-XY19LF	E	E D C B A	
85761-XY10LF	E X X X C X C X X C X X C X X X C X X X C X X X C X	85761 – XY20LF	E X SEE C X SEE NOTE 2	E D C B A	
WHEN "1" or '2" or '3	SELECTIVE LOADING OR NOT WITH ONLY ONE CONTACT RPU LENGTH 5" In Tables : Selective Loading or not but with different RP CATES THE CONTACT TYPE ( TERMINATION LENGTH)		V   F		±0.1 size Scale ±0.1 A2 1
2 CUSTOMER RESPONSIBI RETENTION ON BOARD	ILITY FOR GOOD ALIGNMENT AND		R LS0 S LS0	5-0070 [LO] 055/09/20 [FC] METRAL RCP STR PFIT 5rows 6-0071 [LO] 2006/07/20 [FC] 5x6 SiGNAL - Flat rock	ू इ C-85761-02

PDM: Rev:V

STATUS Released | Printed: Oct 01, 2010

Copyright FCI.