

162...180

862...180

Dimensions: .019 DIA., .057 DIA., .046 DIA., .020 DIA., B, .142, .110, .140, .117, .104, .110, .399

- High density DIP headers and strips for devices featuring .070" lead spacing.
- Series 162 DIP headers use MM #6218 pins. See page 175 for details.
- Series 862 strip headers use MM #6218 pins. See page 175 for details.
- Insulators are high temperature thermoplastic.

| Total number of pins | | | | Quantity per tube | Ordering Information |
|----------------------|---|---|---|-------------------|-----------------------------|
| | A | B | C | | |

| | | | | | | |
|----|-------|------|------|----|----------------------|---|
| 16 | 0.572 | 0.3 | 0.39 | 35 | 162-XX-316-00-180000 | <p style="font-size: small; color: blue;">For RoHS compliance select ◇ plating code.</p> |
| 28 | 0.992 | 0.4 | 0.49 | 20 | 162-XX-428-00-180000 | |
| 30 | 1.062 | 0.4 | 0.49 | 18 | 162-XX-430-00-180000 | |
| 48 | 1.692 | 0.4 | 0.49 | 12 | 162-XX-448-00-180000 | |
| 20 | 0.712 | 0.6 | 0.69 | 28 | 162-XX-620-00-180000 | <div style="border: 1px solid black; border-radius: 50%; padding: 10px; display: inline-block;"> <p style="font-size: small; color: blue;">For Electrical, Mechanical & Environmental Data, See pg. 4</p> </div> <div style="border: 1px solid black; border-radius: 50%; padding: 10px; display: inline-block; margin-left: 20px;"> <p style="font-size: small; color: blue;">XX=Plating Code See Below</p> </div> |
| 28 | 0.992 | 0.6 | 0.69 | 20 | 162-XX-628-00-180000 | |
| 40 | 1.412 | 0.6 | 0.69 | 14 | 162-XX-640-00-180000 | |
| 42 | 1.482 | 0.6 | 0.69 | 13 | 162-XX-642-00-180000 | |
| 48 | 1.692 | 0.6 | 0.69 | 12 | 162-XX-648-00-180000 | |
| 52 | 1.832 | 0.6 | 0.69 | 11 | 162-XX-652-00-180000 | |
| 56 | 1.972 | 0.6 | 0.69 | 10 | 162-XX-656-00-180000 | |
| 64 | 2.252 | 0.6 | 0.69 | 9 | 162-XX-664-00-180000 | |
| 68 | 2.392 | 0.6 | 0.69 | 8 | 162-XX-668-00-180000 | |
| 64 | 2.252 | 0.75 | 0.84 | 8 | 162-XX-764-00-180000 | |

| | | | | | SINGLE ROW STRIP HEADER |
|--|-------|-------|------|---|--------------------------------|
| If desired, we will supply any length up to 21 pins. | | | | | |
| 21 | 1.482 | - - - | .104 | - | 862-XX-121-00-180000 |

| SPECIFY PLATING CODE XX= | 10◇ | 90 | 40◇ | |
|--------------------------|---------|-------------|----------|--|
| Pin Plating | 10μ" Au | 200μ" Sn/Pb | 200μ" Sn | |