

DV6200TD Series Tubeaxial

Ø 172x51mm TURBOFAN



- DC electronic fan with 3 phase EC drive and fully integrated operating electronics. For load-dependent speed control with highly intelligent motor management and power and speed reserves which open up completely new areas of application.
- Mounting from either face using four 4.3 mm holes.
- Metal fan housing, impeller of fiber-glass reinforced plastic PA.
- Air exhaust over struts. Rotational direction CCW looking at rotor.
- Electrical connection via leads. AWG 22, TR 64. Stripped and tinned ends. Housing ground lug for screw M4 x 8 (TORX).
- UL, CSA, VDE approvals on most models, please contact application engineering.

Part Number	Curve	CFM @ 0	VDC	Volt. Range	Power (W)	dBA	Max Amb. Temp. C	Bearing Type	Features	Speed (RPM)	Wgt. (lbs)
min ▼ max	DV6224TD	1	58.9	24	16 to 36	2.0	29	Ball	Leads	800	1.81
		2	412.0			86.0	69			5500	
min ▼ max	DV6248TD	1	58.9	48	40 to 55	2.0	29	Ball	Leads	800	1.81
		2	412.0			86.0	69			5500	

Temperature control available upon request.
Speed setting via control voltage or PWM signal available upon request.

