

PDM: Rev:S STATUS: Released Printed: Feb 06, 2008

		1	2 3	
	PRODUCT NO NOTE 8	PLATING CONTACT AREA	PLATING SOLDER TAIL	
- \ \	68683-2XX	15u"/.38u Au MIN OVER 50u"/1.27u Ni MIN	100µ"/160µ" _{SN} 2.54µ/4.06µ	SEE NOTE 11
/	68683–3XX	30u"/.76u Au MIN OVER 50u"/1.27u Ni MIN	100µ"/160µ"SN 2.54µ/4.06µ	SEE NOTE 11
	68683-4XX	100μ"/160μ" _{SN} 2.54μ/4.06μ	100µ"/160µ"SN 2.54µ/4.06µ	
	68683-6XX	30u"/.76u Au MIN OVER 50u"/1.27u Ni MIN	100µ"/160µ"SN 2.54µ/4.06µ	SEE NOTE 11
	6 8683–8XX	30u"/.76u Au MIN OVER 50u"/1.27u Ni MIN	100µ"/160µ" 2.54µ/4.06µ	OBSOLETE
Δ				-

A

()

FC mect.com

 $(\overline{)}$

С

EO O

Copyright

()

D

form: A3




FIGURE A

2

1

- NOTES:
- 1. MATERIAL TERMINAL: PHOSPHOR BRONZE,
- 2. RECOMMENDED APPLICATION DATA:
 - A. RECOMMENDED HOLE PATTERN IS SHOWN IN FIGURE A.

51

Α

С

- B. ALL MATING PINS TO BE .025/.64 SQUARE ON TRUE CENTER OF GIVEN TERMINAL SPACINGS WITHIN .015/.38 DIA.
- C. SUGGESTED MATING PIN LENGTH .210±.020/5.33±.51
- D. RECOMMENDED PC BOARD THICKNESS: .062/1.58
- (3) MATERIAL HOUSING P.P.S. FILLED, COLOR BLACK, FLAME RETARDENT PER UL 94V-0 THIS PART WILL WITHSTAND EXPOSURES TO 260°C PEAK TEMPERATURE FOR 20 SECONDS IN WAVE SOLDER, INFRA-RED OR VAPOR PHASE SOLDER PROCESS.
- 4 FCI, FCI FINAL PART NUMBER AND DATE CODE TO BE MARKED ON TUBE LABEL.
- 5. PREPLATED, STAMPED TERMINALS.

mat'l. code

sheet revision

sheet

index

3

S

Itr ecn no dr date

- 6. PART NUMBER WITH SUFFIX "U" IS FOR SAWING PURPOSES ONLY.
- (7) STANDARD TUBE PACKAGE PER BUS-14-097/3.
- (8) ADD LF SUFFIX AT THE END OF PART NUMBER FOR LEAD FREE OPTION.
- 9. THESE PRODUCTS MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATION AS DESCRIBED IN GS-22-008.
- (1)."THIS PRODUCT HAS 100% TIN PLATING IN THE INTERFACE AND HAS NOT BEEN TESTED FOR WHISKER GROWTH IN ALL INTERCONNECT ENVOIRNMENTS".

surface

angles

0°±2*

engr

appd

chr

4

ISO 1302 🗸

(1). PLATING OPTIONS:

MAY BE EITHER GOLD OR GXT PLATED AT MANUFACTURER'S OPTION.

liso 1101

linear .xxx ±.005/.13

tolerances unless otherwise specified

dr | J. SHREINER | 02/05/91

M. HAHN

M. HAHN

M. HAHN

tolerance

.XX ±.01/.3

02/05/91

02/05/91

02/05/9

.xxxx ±.0020/.051 scale 4:1

5|

projection product family

title

dwg no

⊕-⊖

INCH/MM

FC

¥,

DUBOX

DUBOX DBL. ROW VERT.

CARD CONNECTOR ASS'Y.

type Product Customer Drawing

68683

sheet2 of 4 size

Аз

6

			1	2 3	
F	RODUCT NUMBER	NO. OF POSITION	C DIM	D DIM	LF OPTION
(68683-Y02	2 X 2	.100/2.54	.217/5.51	
	-Y03	2 X 3	.200/5.08	.317/8.05	
	-Y04	2 X 4	.300/7.62	.417/10.59	
	-Y05	2 X 5	.400/10.16	.517/13.13	
	-Y06	2 X 6	.500/12.70	.617/15.67	
	-Y07	2 X 7	.600/15.24	.717/18.21	
<u> </u>	-Y08	2 X 8	.700/17.78	.817/20.75	
	-Y09	2 X 9	.800/20.32	.917/23.29	
	-Y10	2 X 10	.900/22.86	1.017/25.83	
	-Y11	2 X 11	1.000/25.40	1.117/28.37	
	-Y12	2 X 12	1.100/27.94	1.217/30.91	
	-Y13	2 X 13	1.200/30.48	1.317/33.45	NOTE 8
	-Y14	2 X 14	1.300/33.02	1.417/35.99	
	-Y15	2 X 15	1.400/35.56	1.517/38.53	
3	-Y16	2 X 16	1.500/38.10	1.617/41.07	
com	-Y17	2 X 17	1.600/40.64	1.717/43.61	
hect.	-Y18	2 X 18	1.700/43.18	1.817/46.15	
FClconnec	-Y19	2 X 19	1.800/45.72	1.917/48.69	
	-Y20	2 X 20	1.900/48.26	2.017/51.23	
	-Y21	2 X 21	2.000/50.80	2.117/53.77	
	-Y22	2 X 22	2.100/53.34	2.217/56.31	
	-Y23	2 X 23	2.200/55.88	2.317/58.85	
с	-Y24	2 X 24	2.300/58.42	2.417/61.39	
6	58683-Y25	2 X 25	2.400/60.96	2.517/63.93	v

(_____

IPR.			1	2	LF		4		5	
	RODUCT NUMBER	NO. OF POSITION	C DIM	D DIM	OPTION					
6	8683-Y26	2 X 26	2.500/63.50	2.617/66.47						
	-Y27	2 X 27	2.600/66.04	2.717/69.01						
	-Y28	2 X 28	2.700/68.58	2.817/71.55						
	-Y29	2 X 29	2.800/71.12	2.917/74.09						
	-Y30	2 X 30	2.900/73.66	3.017/76.63						
	-Y31	2 X 31	3.000/76.20	3.117/79.17						
АL	-Y32	2 X 32	3.100/78.74	3.217/81.71						
	-Y33	2 X 33	3.200/81.28	3.317/84.25						
	-Y34	2 X 34	3.300/83.82	3.417/86.79						
	-Y35	2 X 35	3.400/86.36	3.517/89.33						
	-Y36	2 X 36	3.500/88.90	3.617/91.87						
	-Y37	2 X 37	3.600/91.44	3.717/94.41						
	-Y38	2 X 38	3.700/93.98	3.817/96.95	NOTE 8					
	-Y39	2 X 39	3.800/96.52	3.917/99.49						
	-Y40	2 X 40	3.900/99.06	4.017/102.03						
вГ	-Y41	2 X 41	4.000/101.60	4.117/104.57	-					
E	-Y42	2 X 42	4.100/104.14	4.217/107.11						
ot.co	-Y43	2 X 43	4.200/106.68	4.317/109.65						
FClconnect.com	-Y44	2 X 44	4.300/109.22	4.417/112.19						
Clco	-Y45	2 X 45	4.400/111.76	4.517/114.73						
	-Y46	2 X 46	4.500/114.30	4.617/117.27						
	-Y47	2 X 47	4.600/116.84	4.717/119.81						
	-Y48	2 X 48	4.700/119.38	4.817/122.35						
	-Y49	2 X 49	4.800/121.92	4.917/124.89						
c 6	8683-Y50	2 X 50	4.900/124.46	5.017/127.43						
	8683-Y50U	2 X 50	4.900/124.46	5.017/127.43		SEE NOTE 6				

(_____